

12 **EUROPEAN PATENT APPLICATION**

21 Application number: 89304779.5

51 Int. Cl.4: G06F 15/42

22 Date of filing: 11.05.89

The title of the invention has been amended
(Guidelines for Examination in the EPO, A-III,
7.3).

30 Priority: 12.05.88 US 194018
02.06.88 US 201779

43 Date of publication of application:
23.11.89 Bulletin 89/47

84 Designated Contracting States:
AT CH DE ES FR GB GR IT LI NL SE

71 Applicant: **HEALTH TECH SERVICES CORPORATION**
255 Revere Drive Suite 120
Northbrook Illinois(US)

72 Inventor: **Kaufman, Stephen B.**
1939 Lewis Avenue
Highland Park Illinois 60035(US)
Inventor: **Hyland, Shelly**
4619 Daisy
Crystal Lake Illinois 60012(US)
Inventor: **Lesczynski, Michael A.**
725 Shepard Road
Gurnee Illinois 60013(US)
Inventor: **Bryant, Cal L.**
718 Morning Glory Lane
Bartlett Illinois 60103(US)

74 Representative: **MacGregor, Gordon et al**
ERIC POTTER & CLARKSON 14 Oxford Street
Nottingham, NG1 5BP(GB)

54 **Interactive patient assistance system.**

57 A system is provided for interactively assisting a patient. The system includes a speech synthesizer and recognition unit coupled to a programmed computer. The computer can keep track of a medication and diagnostic testing schedule. The system also includes diagnostic testing equipment coupled to the computer along with medication dispensing equipment. In accordance with a predetermined schedule, the system verbally communicates with the patient, prompts the patient through the various steps necessary to carry out the diagnostic testing and further prompts patient at appropriate times for taking medication. The medication is also provided in combination with the verbal prompts. The system also provides access to a telecommunications link in response to verbal requests of the patient and in one embodiment can move in a limited area adjacent the patient.




Fig. 3

Xerox Copy Centre

EP 0 342 859 A2

MULTI-CONTAINER INTERACTIVE SYSTEM

Reference to Related Patent Application

The present patent application is a continuation-in-part of patent application Serial No. 194,018 filed May 12, 1988 entitled INDIVIDUAL ASSISTANCE SYSTEM and assigned to the same assignee as the present application.

Field of the Invention

The invention pertains to apparatus and devices for assisting individuals. More particularly, the invention pertains to a computer based system for providing at home or institutional assistance to a convalescing or injured patient.

Background of the Invention

Over the last several years, there has been a substantial shortening of the period of time patients remain in hospitals. Reductions in hospital stays are directly related to the Federal Medicare Regulations governing reimbursements to hospitals and other institutions. These regulations impose strict limits on the number of hospital days, or institution days, for which Medicare will reimburse the hospital or institution.

Due to the shortened hospital stays, many patients are returning home in a debilitated or partially recovered condition. These patients often need assistance or reminders that medication should be taken, or that various measurements such as temperature or blood pressure should be made.

This situation is exacerbated by the fact that the size of the population which is over 65 years of age is continually increasing and will be increasing for the foreseeable future. In addition, because of the improved health care delivery system in general, patients with chronic diseases are surviving for longer periods of time and leading relatively normal lives with intermittent outpatient intervention.

It has also been recognized that patients who need follow-up or who are convalescing at home can benefit from regular home monitoring. Such monitoring provides follow up information concerning the condition of the patient.

For instance, home monitoring can provide information concerning the long-term effectiveness of drugs. This information can in turn lead to altering, increasing or decreasing prescription requirements to more cost effectively obtain the desired result with the patient.

Home monitoring can also provide long-term trend information concerning patient vital signs. In extreme cases, home monitoring can result in immediate intervention to avoid a life threatening situation.

Thus, there continues to be a need for devices and apparatus which would be of assistance to homebound patients in a variety of ways. Further, there continues to be a need for such devices which can be provided cost-effectively.

Summary of the Invention

In accordance with the invention, a patient assistance system is provided for repetitively interacting with an individual in need of assistance. The system can provide a variety of functions useful to an individual who may be debilitated or convalescing from an injury or an illness.

The system includes a control unit which can provide a variety of patient support functions. A programmable clock/calendar readout is coupled to the control unit. The clock/calendar unit can be programmed to perform reminder functions at predetermined times. For example, the clock/calendar unit can provide a wake-up alarm, can regulate medication dispensing, or can keep track of times at which tests should be carried out.

An audible alarm or visual indicator can be provided as a reminder of when an activity should be commenced. The audible alarm can also be used to introduce an audible synthesized message.

The system also includes voice synthesizer circuitry for the purpose of generating audible messages. The messages can remind the patient of specific, preprogrammed, tasks to be performed at predetermined times. For example, the voice synthesizer circuitry, in combination with the control unit, can remind the

patient that it is time to take medication or carry out a monitoring test such as taking a temperature or a blood pressure.

The voice synthesizer circuitry can also be used to communicate with the patient when the preprogrammed schedule needs to be varied. That circuitry can also prompt verbal responses usable to determine
5 general patient condition.

Speech detection circuitry can be used to analyze those responses or requests. That circuitry can then signal the control unit with an identification of those responses.

The voice recognition and synthesis circuitry can be used to verify, via audio feedback from the patient that certain tasks have been successfully performed. These include taking medication or conducting various
10 tests.

As an alternate, a keyboard could be used for operator input instead of voice recognition circuitry. Instead of a keyboard a touch-sensitive screen can be used.

The system can also include sound and motion detecting systems. The sound detection system, coupled to the control unit, can detect ultrasonic transmissions from a patient transmitter such as a
15 medallion or a wrist transmitter. The sound detection system can also detect and enable the control system to respond to requests by the patient for assistance.

A moveable embodiment of the system includes an ultrasonic collision avoidance system. The ultrasonic system can determine distance, range and proximity of objects for collision avoidance purposes. Further, the ultrasonic system enables the patient assistance system to move within a specified region near
20 the patient to provide for easy accessibility thereto.

The system can also include an interface between the control unit and a telephone. In response to commands from the control unit, the interface can provide for automatic dialing in response to patient requests or in response to detected emergency conditions.

The system also includes a printer for generating a hard copy record of daily medical information
25 including test results as well as delivery of medication. A recording system can store that information in machine readable form.

A modem is coupled to the automatic dialer in the interface. The modem can be used for the purpose of communicating with a remote medical computer, for transferring patient information to the remote computer or for receiving programmed instructions or information from the remote computer.

Further in accordance with the invention, a method of interacting with a care requiring individual is provided. The method includes the steps of:

- detecting audio emergency requests for help from the individual;
- detecting when the individual should receive predetermined medication;
- making the predetermined medications available to the individual in accordance with a predetermined
35 schedule;
- verifying that the predetermined medications have been received by the individual;
- recording electronically the fact that the medications have been provided as well as the fact that an indicium has been received that the medications were received by the individual;
- reminding the individual to carry out certain predetermined monitoring tests at predetermined time intervals;
- 40 recording electronically results of the predetermined tests;
- automatically dialing a predetermined number to establish a communication link with a remote information receiving unit; and
- transferring the results of the monitoring test step to the remote unit.

Numerous other advantages and features of the present invention will become readily apparent from the
45 following detailed description of the invention and the embodiments thereof, from the claims and from the accompanying drawings in which the details of the invention are fully and completely disclosed as a part of this specification.

50 Brief Description of the Drawings

Figure 1 is a perspective view of a stationary recordkeeping and medication delivery interactive system in accordance with the present invention;

Figure 2 is a perspective view of a moveable recordkeeping and medication delivery interactive
55 system in accordance with the present invention;

Figure 3 is a block diagram schematic of an electronic system in accordance with the present invention.

Figure 4 is an overall perspective view of a system in accordance with the present invention interacting with a patient;

Figure 5 is a fragmentary perspective view of the system of Figure 4 supported on a powered module for movement;

5 Figure 6 is a rear elevational view of the system of Figure 4;

Figure 7 is an enlarged fragmentary view in perspective of a portion of the thermometer storage/delivery unit;

Figure 8 is an enlarged fragmentary view in perspective of a portion of the product storage/delivery unit;

10 Figure 9 is an enlarged fragmentary view in perspective, partly broken away, of the actuating mechanism of the storage/delivery unit of Figure 7;

Figure 10a is a view in section illustrating a first or inactive state of the product dispensing mechanism;

Figure 10b is a view in section of the product dispensing mechanism in a second or dispensing state;

15 Figures 11a-11e, taken together, are a flow diagram of the software and interactions of the system of Figure 4;

Figure 12 is an overall block diagram-schematic of the electronic control system of the system of Figure 4;

20 Figure 13 is a detailed electronic schematic of a portion of the interface circuitry of the system of Figure 4; and

Figures 14a and 14b, taken together, are a detailed electronic schematic of another portion of the interface circuitry of the system of Figure 4.

25 Detailed Description of the Preferred Embodiments

While this invention is susceptible of embodiment in many different forms, there are shown in the drawing and will be described herein in detail specific embodiments thereof with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and is not intended to limit the invention to the specific embodiments illustrated.

Figure 1 is a perspective view of a patient assisting system 10 in accordance with the present invention. The system 10 includes a housing 12. carried by the housing 12 is a video display unit 14.

The system 10 includes a clock/calendar unit 16. The clock/calendar unit 16 can be a digital unit with an integrally formed display.

35 The housing 12 carries an audible alarm 16a. The audible alarm 16a can be actuated by the electronic clock/calendar unit 16. The clock/calendar unit can be a programmable unit in which a schedule can be established to identify a variety of scheduled activities during a 24-hour interval. A display 16b is also coupled to the clock/calendar unit 16.

40 The housing 12 also carries a hard copy printer 18 capable of generating hard copy 20. The copy 20 can include information pertaining to medication schedules, delivered medication, test results or instructions as may be desired.

The system 10 can also include a blood pressure monitoring cuff storeable in a region 24 of the system 10. The same cuff can be used for pulse rate detection as well.

45 The system 10 can also include a thermometer 28 coupled thereto. The thermometer 28 can be drawn from the system 10 and used by the patient to provide an indication of corporal body temperature. The thermometer 28, the blood pressure cuff and the pulse rate sensor can be used to provide feedback to the system 10 concerning patient related characteristics. Temperature and blood pressure measurement values can be displayed using readouts 29.

50 The system 10 also includes a pharmaceutical dispenser 30. The pharmaceutical dispenser 30 can under control of the system 10 dispense medication on a strip 32 in accordance with a schedule maintained by the programmable clock/calendar unit 16.

55 The medication on the strip 32 can be dispensed in combination with either a printed reminder which can be printed by the printer 18 on the strip 20 or in combination with a verbal reminder. A voice synthesizer and recognition unit 36 carried by the housing 12 can provide audio reminders to the patient that a scheduled time for taking a medication has arrived. The unit 36 can provide audible feedback from the patient to the system 10.

For example, the voice synthesizer and recognition unit 36 can detect statements made by the patient requesting assistance. These statements can include requests for help if the patient is in need of outside

assistance. Alternately, the voice synthesizer and recognition unit 36 can detect requests by the patient to display information on the display 14 or to provide the appropriate medication. Finally, the voice synthesizer and recognition unit 36 can be used by the patient to establish the schedule to be maintained by the programmable clock/calendar unit 16.

5 It will be understood that in addition to detecting blood pressure, heart rate and body temperature, the system 10 could provide facilities for detecting blood gas levels as well as carrying out other types of non-invasive diagnostic tests. For example, one type of diagnostic testing that can be carried out in connection with the system 10 make use of known oximetry probes. Such probes can be attached to the ear lobe or finger of the patient and provide for continuous or intermittent reading of oxygen saturation levels in the blood.

The system 10 also incorporates a modem 40 which can be utilized in combination with an automatic dialer unit 42. The modem 40 could incorporate a standard type of telephone handset 44 if desired. By incorporating a handset 44, the system 10 can provide for a voice communication between the patient and a remote location.

15 By means of the modem 40, the system 10 can communicate with a remote medical center over the telephone system. Information which has been accumulated in the system 10 concerning patient activity or the results of diagnostic testing can be automatically transmitted via the modem 40 and the telephone system to a remote medical center computer for analysis. The results of such analysis can be used to determine whether or not further intervention, such as changing the medication schedule or the type of medication, is desirable.

The system 10 can also include a magnetic recording system. The recording system can record, on a relatively long-term basis, results of diagnostic tests, information concerning patient activity, dispensed medication and any other information of value in improving the quality of patient care.

The various elements of the system 10 function with a control unit 46. The control unit 46 could include a programmed computer.

Figure 2 illustrates a perspective view of an alternate embodiment 50 of the system 10. The system 50 includes many of the functions and capabilities previously described with respect to the system 10. Such elements are identified using the same identification numerals as were used with respect to the system 10.

In addition, the system 50 provides additional capabilities and functions not present in the system 10. The system 50 in contradistinction to the system 10 is moveable under the command of the internal programmed control computer 46. The moveability of system 50 permits it to move toward the bedside or chair of the patient for ease of interaction with the patient.

Control over the movement of the system 50 by the computer 46 is effected by an ultrasonic system 52. The ultrasonic system 52 includes both a transmitter and a receiver 52a and 52b respectively. The ultrasonic system 52 can detect transmission from a patient-carried transmitter. The patient-carried transmitter can be used to inform the system 50 of the location of the patient. It can also be used to detect whether or not the patient is ambulatory and whether or not the patient has had an accident and has fallen and is in need of additional assistance.

The ultrasonic system 52 can also determine distance, range and proximity to objects for the purpose of collision avoidance. The ultrasonic system 52 also permits the patient assisting system 50 to safely move within a specified range near the patient.

The system 50 also includes a nasal cannula 54 usable in connection with administering oxygen therapy. Further, the system 50 can also include a probe 56 for measuring saturated oxygen levels in the blood, as previously discussed. Such probes, such as 56, are noninvasive and can readily be affixed by the patient to the appropriate corporal member.

The system 50 also includes a digital blood pressure sensing cuff 60 which can be removed from the storage region 24. The patient can apply the cuff 60 to an arm or finger or any other appendage. Under control of the system 50, the cuff 60 can be automatically inflated, the results of the blood pressure measurement can be detected by means of the monitoring function input interface 48. The cuff 60 can then be deflated and removed by the patient for storage in the region 24.

Simultaneously with detecting blood pressure by means of the cuff 60, the patient's pulse rate can also be detected.

The system 50 includes the voice synthesis and recognition unit 36 which provides an audio communication and control path between the patient and the system 50. A battery 64 is carried within the housing 50a for the purpose of powering the unit 50. The battery 64 can be a rechargeable type which can be recharged during periods of patient inactivity, such as night.

If desired, the handset 44 can be of the cordless type. In this instance, the system 50 would also carry a transmission/reception antenna 66.

It will be understood that the system 50 functions at all times under the control of the programmable unit 46 to insure proper carrying out of the above described functions. Further, by means of the voice synthesis and recognition unit 36 the patient is always able to provide verbal commands to the unit 50.

Further in accordance with the invention, Figure 4 illustrates as an alternate embodiment, a system 100 in accordance with the principles of the present invention. The system 100 is being utilized by a patient P for purposes of carrying out a diagnostic test. Many of the elements of the system 100 correspond to elements of the system 10 and the system 50. Corresponding elements have been identified with the same identification numerals as were used in Figures 1 and 2.

The system 100 includes a housing 102. The housing 102, at an upper surface 102a, can support an optional display unit 14, indicated in phantom. The housing 102 also carries an alphanumeric display 104. The alphanumeric display 104 can be used to conveniently display the results of various diagnostic tests which can be performed by the system 100.

In particular, the system 100 is illustrated in Figure 4 with the patient P using a finger type blood pressure and pulse rate cuff 106. The cuff 106 can be used to detect the blood pressure and pulse rate of the patient P.

Supported on an upper surface 108 of the housing 102 is a telephone corresponding to the telephone 44. It will be understood that a variety of different telephones can be used without departing from the spirit and scope of the present invention.

Also carried on the surface 108 is a loudspeaker 110 which is coupled to the voice synthesis and recognition unit 36 discussed previously. A hands-free microphone 112 is also provided, coupled to the voice synthesis and recognition unit 36, for purposes of audio input by the patient P.

The housing 102 also supports a plurality of visual indicators 120a, 120b and 120c. The indicators 120a, 120b and 120c are usable in conjunction with a plurality of moveable storage/delivery units 124a, 124b and 124c.

The storage/delivery units 124a, 124b and 124c can be used for storage and delivery of a plurality of different items. For example, the unit 124a is illustrated in the system 100 as being the storage/delivery unit for the finger type cuff 106. The indicator 120a is utilized to prompt the patient P to the fact that the unit 124a has been released and the cuff 106 should be removed therefrom and inserted on the patient's finger for purposes of conducting a diagnostic test.

The unit 124b can be used for storage and delivery of a thermometer. The unit 124c can be used for storage and delivery of prescheduled products. The products can include medications in either liquid or solid form.

It will be understood that the types of apparatus and/or products, described above, utilized with the units 124a, 124b and 124c are merely exemplary. The exact type of apparatus stored or product delivered is not a limitation of the present invention.

The housing 102 also carries a manually operable, illuminatable signaling button or switch 126. The button or switch 126 can be used by the patient P to inform the system 100 that various activities have taken place or that various conditions have been met.

For example, the button or switch 126 can be used to prompt the system 100 to the fact that the patient has placed the cuff 106 on a finger and is ready for a blood pressure measurement to be made. Similarly, the switch 126 can be used to prompt the system 100 to the fact that the thermometer has been properly positioned and a temperature reading can be made. Finally, the button or switch 126 can be used to prompt the system 100 to the fact that a product, such as a medication, has been removed from the unit 126 and has been taken by the patient P.

While the system 100 has been illustrated in Figure 4, supported on a plurality of rollable casters 130, it will be understood that, in accordance with the embodiment previously discussed in Figure 2, the system 100 could be provided with a motorized unit for purposes of movement.

Figure 5 illustrates an exemplary motorized unit 132. The unit 132 carries the housing 102. The unit 132 includes a motor, control electronics and power source 134. The unit 134 can be mechanically coupled to drive wheels 136 for the purpose of moving the system 100 toward or away from the patient P.

Figure 6 is a view of the rear of the housing 102 illustrating various components of the system 100. The housing 102 defines an interior region 140 wherein the components of the system 100 are carried.

The system 100, as discussed previously with respect to Figures 1 and 2 includes a programmable control computer 46. The computer 46 can be of a type comparable to IBM[®]-PC-XT or other computer system capable of performing multi-tasking. The unit 46 can include an interface for driving the display 14, if present, by the system 100. The unit 46 can also include the programmable clock/calendar unit 16.

The unit 46 can also include a disc drive controller.

Disc storage 142 can be located within the housing 102 adjacent the computer 46. The disc storage

142 can include a hard drive and one or more floppy drives depending on the desired capacity of data storage.

The computer 46 can also include the modem 40. The modem 40 could be for example a 1200 baud Hayes brand modem.

5 Adjacent the disc storage 142 is a system power supply 144. The supply 144 can include a rechargeable battery.

The voice synthesis/recognition unit 36 is also located adjacent the control computer 46. The voice synthesis/recognition unit 36 could be for example, a Texas Instruments Recognition and Speech Unit Model TI-2245186-001.

10 An interface card 146 is also provided adjacent the control computer 46. The interface card 146 provides part of the circuitry used for driving solenoids to control the units 124a, 124b or 124c as well as the displays 120a, 120b and 120c. For example, the unit 146 could be a Quatech Analogue input card or equivalent as would be known by those of skill in the art.

The housing 102 also carries electrical interface circuitry 148. The circuitry 148 converts signals from 15 the measurement cuff 106 to electrical signals usable by the monitoring function unit 48.

The housing 102 also carries the printer 18 for a generation of hard copy records 20 or graphical diagrams.

Figure 7 is a perspective, fragmentary, view illustrating the storage/delivery unit 124b in the delivery position. In the exemplary unit illustrated in Figure 7, the unit 124b is a multi-sided drawer with a bottom 20 150a joined by four sides 150b, 150c, 150d and 150e.

It will be understood that the exact shape of the storage/delivery unit 124b is not a limitation of the present invention. A variety of different shapes could be used which would function in substantially the same way to produce substantially the same results.

Carried within the unit 124b is a thermometer 152. The thermometer 152 is coupled by conductors 154 25 to the monitoring function interface unit 48.

As illustrated in Figure 7, the indicator 120b has been energized indicating to the patient P that the system 100 is awaiting the withdrawal of the thermometer 152 from the unit 124b and the subsequent actuation by the patient of the control button 126.

As illustrated in Figure 4, the unit 124b has a first, or closed, position. The unit 124b also has a second, 30 or open, position as illustrated in Figure 7. Each of the units 124a and 124c has corresponding first and second positions.

Figure 8 illustrates the unit 124c in its second, or open, position. The indicator 120c has been energized indicating to the patient P that a product such as medication M in unit 124c is available and can be accessed in the drawer 124c. It will be understood that while medication M has been illustrated in solid, or 35 pill form, in Figure 8 that the exact form of the dispensed product is not a limitation of the present. The product need not be a medication or alternately could be in liquid form.

Figure 9 is a fragmentary enlarged view of the unit 124b along with an associated electrically operated release mechanism 160. The release mechanism 160 could be an electrically actuated spring biased solenoid of a conventional type.

40 When energized, a locking member, or armature, of the solenoid 160 retracts by moving in an unlocking direction 162. Once the solenoid 160 has retracted, the unit 124b is forced to its second, or open, position by means of a spring biasing unit 164.

The unit 164 includes a support housing 166. The housing 166 includes an internal, compressed, biasing spring 168. The spring 168, in response to the solenoid 160 having energized its armature which 45 moves in the releasing direction 162, forces the unit 124b to move in a direction 170a from the first, closed position to the second, open position. The unit 124b can be returned to the first, or closed position by manually forcing it in a direction 170b until the solenoid 160 relatches it.

Figures 10A and 10B are enlarged fragmentary sectional views illustrating the structure and operation of the product dispensing unit 124d. The unit 124d includes a housing 174 which defines a product containing 50 volume 174a.

Within the product containing volume 174a can be stored a plurality of products corresponding to the medication M. In the illustrative embodiment of Figures 10A and 10B, the product corresponds to individually dispensed medication units or pills.

The housing 174 has a lower open end 176. The end 176 defines a product releasing opening 178 55 therein. A single product releasing index member 180 is positioned adjacent the end 176 of the housing 174.

The index member 180 also defines a single product containing region 182 therein. Affixed to the housing 174 is a fixed delivery member 184. The delivery member 184 includes a product delivery ramp

184a.

As illustrated in Figure 10B, the index plate 180 can be moved laterally in a direction 180a in response to the control unit 46 actuating an electrical solenoid. The movement of the indexing unit 180 dispenses the product M1 located in the region 182 as illustrated in Figure 10B. At the same time, movement of the indexing plate 180 blocks other products M in the region 174a from being dispensed simultaneously. The product M1 when released from the indexing member 180 can slide down the delivery shut 180a and into the unit 124c for subsequent removal and use by the patient P.

At the end of the release cycle the indexing unit 180 returns to its rest position illustrated in Figure 10A by moving opposite to the direction 180a. The cycle may then be repeated. The next time the solenoid is energized, the index unit 180 will again move in the direction 180a and dispense a single product to the unit 124c.

It will be understood that the exact structure of the dispensing mechanism 124b is not a limitation of the present invention. Nor, is the type of product to be dispensed a limitation of the present invention.

Figures 11A through 11E, taken together, are a flow diagram illustrating the steps of a method of operation of the system 100 and its interactions with the patient P. the flow diagram of Figures 11A-11E also defines the control program to be used with the control computer 46 to implement the functioning of the system 100.

Attached hereto as an Addendum is a listing of a program usable with the system 100. The first group of instruction, up to line 400 of the Addendum, is a plurality of interface sub-routines to enable the processor 46 to interact with various of the interface devices. The portion of the program from line 400 on to the end is written in BASIC and is the control program for the system 100.

Figure 12 is a block diagram schematic of the system 100. As noted previously, the processor 46 or central processing unit is comparable to an IBM[®]-PC-XT class computer. The power supply 144 coupled thereto is of an uninterruptable type having a self-contained rechargeable battery.

The processor 46 is coupled via an address bus 200 and a data bus 202 to a plurality of input/output units. Among those units is a modem 40a which includes automatic dial and answer as well as a voice channel for audio communication.

The address bus 200 and data bus 202 are also coupled to solenoid drive circuitry, indicator drive circuitry and medication solenoid drive circuitry 48a. The address bus 200 and the data bus 202 are also coupled to instrumentation interface circuitry 48b. The instrumentation interface circuitry can include the blood pressure/pulse rate cuff 106 thermometer 152, along with optional blood gas analyzer 56 and urine analyzer.

The speech processor circuitry including the voice synthesis/recognition unit 36 as well as voice recorded circuitry is also coupled to both the address bus 200 and the data bus 202. The system 100 also utilizes a 10 megabyte hard disc and a 360 K-byte floppy disc represented by element 142. If desired, the optional display 14 will also be coupled to the address bus 200 and the data bus 202.

The display 14 could also include a keyboard for operator input. Instead of a keyboard, the display 14 could incorporate a touch sensitive screen.

Finally, the system 100 includes 512 K-bytes of main random access memory 206 which utilizes the available battery backup.

Figure 13 is a detailed schematic diagram of the interface circuitry 148 between the cuff 106 and the data bus 202. Acoustic signals from the cuff 106 are detected in a condenser microphone 208. The condenser microphone 208 serves as the electrical input to the circuitry 148. Signals from the microphone 208 are processed in the circuitry of Figure 13 and coupled to the data bus 202.

Figures 14A and 14B, taken together, are a detailed schematic of the driver circuitry 48a.

Elements U1, U2 and U3 are LM3302 type comparators. Elements U4, U5 and U6 are operational amplifiers type LM324. Signals from the address bus 200 and the data bus 202 are received at inputs to the plurality of comparators 210. Outputs from the comparators 210 provide inputs to a plurality of operational amplifiers 212.

Outputs through the operational amplifiers 212, via a plurality of transistor drive circuits 214 provide electrical signals and power levels for an 8-volt regulated supply 216 to power the circuitry for the blood pressure cuff 106, and to illuminate indicators 120a, 120b, 120c and 126a. The drive transistors 214 also provide signals to actuate a cuff venting solenoid 220, a cuff drawer releasing solenoid 222; a thermometer drawer releasing solenoid 224; a dispensed product drawer releasing solenoid 226 and a product dispensing mechanism actuating solenoid 228.

The principles of the present invention, it will be understood, are applicable to computer based systems, with or without speech recognition, usable by persons of good health and sound body. Further, it will be understood that systems in accordance with the present invention can also be used in hospitals or

nursing homes.

From the foregoing, it will be observed that numerous variations and modifications may be effected without departing from the spirit and scope of the novel concept of the invention. It is to be understood that no limitation with respect to the specific apparatus illustrated herein is intended or should be inferred. It is, of course, intended to cover by the appended claims all such modifications as fall within the scope of the claims.

10

```

1  '*****
2  '*
3  '*
4  '*
5  '*
6  '*
7  '*
8  '*****
9  GOTO 560
10 ADC.SETUP=&H91B:ALTOU12.B=&H738:ALTOU12.BT=&H799:ALTOU12.R=&H7FD
11 ALTOU12.RT=&H860:ALTOU12.S=&H6E5:ALTOU12.ST=&H70D:ALTOU8.B=&H2A9
12 ALTOU8.BT=&H335:ALTOU8.R=&H3C7:ALTOU8.RT=&H459:ALTOU8.S=&H220
13 ALTOU8.ST=&H262:DAC.SETUP=&H1A:INADC12.B=&HD5E:INADC12.BT=&HDF1
14 INADC12.EXTCLOCK=&HE94:INADC12.S=&HCE5:INADC12.ST=&HD16:INADC8.B=&H9C3
15 INADC8.BT=&HA31:INADC8.EXTCLOCK=&HAA2:INADC8.S=&H93E:INADC8.ST=&H974
16 OUTDAC12.B=&H550:OUTDAC12.BT=&H5B5:OUTDAC12.R=&H61D:OUTDAC12.RT=&H676
17 OUTDAC12.S=&H4F1:OUTDAC12.ST=&H51F:OUTDAC8.B=&H92:OUTDAC8.BT=&HF3
18 OUTDAC8.R=&H157:OUTDAC8.RT=&H1BA:OUTDAC8.S=&H3F:OUTDAC8.ST=&H67
19 SCAN12.B=&HFFD:SCAN12.BT=&H1095:SCAN12.S=&HFA3:SCAN12.ST=&HF97
20 SCAN8.B=&HBBD:SCAN8.BT=&HC4E:SCAN8.S=&HAFF:SCAN8.ST=&HB54
21 DEF SEG=0
22 CSEG=(256*PEEK(&H3CB))+PEEK(&H3CA)
23 DEF SEG=CSEG
24 '
25 '
26 '
27 '
28 '
29 '
30 '
31 '
32 '
33 '
34 '
35 '*****
36 ADDRESS=&H300 'module address
37 CALL ADC.SETUP(ADDRESS) 'setup address
38 DIM ARRAY$(1000)
39 GOTO 560
40 'ANALOG BOARD SUB *****
41 BCHANNEL=&=0 'beginning channel
42 ECHANNEL=&=4 'end channel
43 TIMING=&=1000 'around 5ms
44 LENGTH=&=1 '1 PASS SCAN
45 SCANNO=&=ECHANNEL-BCHANNEL+1
46 CALL SCANS.B(BCHANNEL,ECHANNEL,TIMING,LENGTH,ARRAY$(1))
47 '
48 PRINT "CHANNEL 0 CHANNEL 1 CHANNEL 2 CHANNEL 3 CHANNEL 4"
49 PRINT
50 FOR I=1 TO LENGTH*SCANNO STEP SCANNO
51 PRINT ARRAY$(I),ARRAY$(I+1),ARRAY$(I+2),ARRAY$(I+3),ARRAY$(I+4)
52 LET V=ARRAY$(I)
53 LET W=ARRAY$(I+1)
54 LET X=ARRAY$(I+2)
55 LET Y=ARRAY$(I+3)
56 LET Z=ARRAY$(I+4)
57 NEXT
58 RETURN 'END OF ANALOG SUB *****
59 '
60 '
61 'CHECK TIME ROUTINE

```

55

```

5  510 DT=2 '**** *
520 T=VAL(MID$(TIMES,4,2))+DT
530 IF T>60 THEN T=T-60
540 IF VAL(MID$(TIMES,4,2))=T THEN 550 ELSE 540
545 GOTO 590
550 '
10 560 SRT=INP(H301) 'PUSH BUTTON TO START
570 IF SRT<=1 THEN GOTO 600 ELSE GOTO 560
580 '
590 'SETUP & DATA **** *
600 '
605 OUT &H30B,&H89 'WAKEUP 8255 AND CONFIG PORTS A&B OUT C IN/OUT
606 OUT &H309,&HF
610 COUNT=1000:COUNT2=3000:REPS=2:PRESSED=1
15 620 HOSP=3663:MARY=3663:DOC=3663 '*****PHONE NUMBERS*****
    0 FLAG1=0:FLAG2=0:FLAG3=0:FLAG4=0:FLAG5=0:FLAG6=0:FLAG7=0:FLAG8=0
640 SYSLO=100:SYSHI=150:DILO=60:DIHI=90 'BLOOD PRESSURE LIMITS
650 PULSLO=60:PULSHI=110 'PULSE LIMITS
660 THIGH=100:TLOW=96.5 'TEMPERATURE LIMITS
670 PULS=80:BPS=90:BPD=60:TEMP=98.6 'TEST DATA
680 OPEN "TISPCH" FOR OUTPUT AS #1:PRINT #1,"RESET"
20 690 PRINT #1, "VOLUME=8"
700 PRINT #1, "LOAD=NAME"
709 PRINT #1, "RECOGNIZE=ON"
710 PRINT #1, "RECOGNIZE=NAME"
711 PRINT #1, "SPEAKFILE=WHO.MSG"
712 FOR L=1 TO COUNT: WHO$=INKEY$:IF WHO$<>" THEN 713 ELSE NEXT L
713 IF WHO$="1" THEN PRINT #1, "LOAD=MIKE":PRINT #1, "RECOGNIZE=MIKE":HELLO$="P"
714 IF WHO$="2" THEN PRINT #1, "LOAD=TAM":PRINT #1, "RECOGNIZE=TAM":HELLO$="TAM"
25 715 IF WHO$="3" THEN PRINT #1, "LOAD=STEV":PRINT #1, "RECOGNIZE=STEV":HELLO$="S"
720 GOTO 711 ' NAME NOT RECOGNIZED
725 '***** *
730 ' WAKEUP CALL
731 PRINT HELLO$
    0 LOOP=0
750 FOR I=500 TO 1000 STEP 250:SOUND I,9:NEXT I
30 755 HOUR1=VAL(LEFT$(TIMES,2)):MIN1=VAL(MID$(TIMES,4,2))
756 IF HOUR1>12 THEN HOUR1=HOUR1-12
760 PRINT #1, "SPEAKFILE=":HELLO$
770 PRINT #1, "SPEAKTEXT=":HOUR1:MIN1: " ."
780 FOR L=1 TO COUNT: ANS$=INKEY$:IF ANS$<>" THEN 790 ELSE NEXT L
790 IF ANS$="Y" THEN 870
800 PRINT LOOP
35 810 IF LOOP>REPS THEN GOTO 820 ELSE 850 'PHONE HOSPITAL
820 FLAG1=1:WHO$="+":NUMB=HOSP:GOSUB 2000
830 'PRINT "PATIENT WON'T RESPOND..PHONE CALL MADE."
840 GOTO 1810
850 LOOP=LOOP+1:GOTO 750
860 ' PATIENT FEELINGS
870 LOOP=0
880 PRINT #1, "SPEAKFILE=FEEL.MSG"
40 890 FOR L=1 TO COUNT: FEEL$=INKEY$:IF FEEL$<>" THEN 900 ELSE NEXT L
900 IF FEEL$="O" OR FEEL$="F" OR FEEL$="G" THEN 1010
910 IF FEEL$="B" OR FEEL$="A" OR FEEL$="T" THEN GOTO 940
920 IF LOOP>REPS THEN GOTO 1000 ELSE LOOP=LOOP+1
930 GOTO 880
940 ' NEGATIVE FEEL RESPONSE - CALL HOSPITAL AFTER TAKING VITALS?
950 PRINT #1, "SPEAKFILE=PHONE.MSG"
45 960 FOR L=1 TO COUNT: PHON$=INKEY$:IF PHON$<>" THEN 970 ELSE NEXT L

```

```

5  970 IF PHONS="Y" THEN FLAG2=1 ELSE 1010 'SET PHONE FLAG
    980 PRINT #1, "SPEAKFILE=VITALS.MSG"
    990 GOTO 1010
    1000 FEELS="NO RESPONSE" 'NO FEELING RESPONSE
    1010 FEELS="NONE" 'RECORD FEELING & GO ON TO BP
    1020 '
    1030 ' BEGIN BP/PULSE PROMPT ROUTINE
    1040 '
10  1050 PRINT #1, "SPEAKFILE=BP.MSG"
    1051 OUT &H308,&H1 'OPENS BP DRAWER
    1052 FOR A=1 TO 200 :NEXT A
    1053 OUT &H308,&H30 'TURN ON BP & START LITE
    1060 PRINT #1, "SPEAKFILE=FINGER.MSG"
    1061 A%=INP(&H30A) :IF A%<=PRESSED% THEN 1062 ELSE 1061
15  1062 PRINT "STARTING BP" :OUT &H309,&H2
    1063 FOR B=1 TO 3: FOR D=1 TO 8000:NEXT D:NEXT B '1 TO 6=1 MIN 45 SEC
    1060 '
    1170 '
    1180 '
    1190 OUT &H309,&H1 :GOSUB 4010 'VENT BP CUFF - BP SUB
    1195 OUT &H309,&HF :OUT &H308,&H0 'TURN BP OFF
20  1200 PRINT #1, "SPEAKFILE=BPOFF.MSG" 'BP DONE
    1201 FOR J=1 TO COUNT2 :NEXT J
    1209 'PRINT #1, "SPEAKFILE=CLOSE.MSG"
    1210 '
    1220 ' TEMP PROMT ROUTINE
    1230 '
    1240 OUT &H308,&H2 'OPEN THERM DRAWER
25  1241 FOR A=1 TO 200 :NEXT A
    1242 OUT &H308,&H50 'TURN ON LITES
    1250 PRINT #1, "SPEAKFILE=TEMP.MSG"
    1260 TLOOP=0
    1265 A%=INP(&H30A):IF A%<=PRESSED% THEN 1270 ELSE 1265
    1266 PRINT "TEMP STARTED."
    1270 FOR G=1 TO COUNT2:NEXT G 'WAIT 30 SEC
30  1280 ' MARKER
    1280 GOSUB 3010 'CALL SUB TO TAKE TEMP.
    1290 IF TLOOP=1 THEN GOTO 1260
    1295 TLOOP=0
    1400 PRINT #1, "SPEAKFILE=TEMPOFF.MSG"
    1401 'FOR J=1 TO COUNT 'CHECK THAT DRAWER IS CLOSED
    1402 'DOOR%=INP(H300)
    1403 'IF DOOR%=PRESSED THEN GOTO 1440
35  1404 'NEXT J
    1406 'IF TLOOP>REPS THEN GOTO 1409 ELSE TLOOP=TLOOP+1
    1407 'GOTO 1400
    1409 'PRINT #1, "SPEAKFILE=CLOSE.MSG"
    1410 '
    1420 ' DISPENSE PILLS ROUTINE
    1430 '
40  1440 PRINT #1, "SPEAKFILE=MED.MSG"
    1450 OUT &H308,&H8 'DROP PILL
    1451 FOR A=1 TO 200 :NEXT A
    1452 OUT &H308,&H0
    1453 FOR A=1 TO 500 :NEXT A
    1454 OUT &H308,&H4 'OPEN PILL DRAWER
45  1455 FOR A=1 TO 200 :NEXT A
    1456 OUT &H308,&H80
    1460 PRINT #1, "SPEAKFILE=PILLS.MSG"
    1461 FOR I=1 TO COUNT:NEXT I

```

50

55

```

5      1462 PRINT #1, "SPEAKFILE=DIDPILL.MSG
      1463 FOR L=1 TO COUNT:DID$=INKEY$:IF DID$="Y" THEN 1480 ELSE NEXT L
      1464 PRINT #1, "SPEAKFILE=DIDPILL2.MSG"
      1465 GOTO 1461
      1480 OUT &H308,&H0 'LITES OFF
      1490 ' PHONE CALL PROMPT ROUTINE
10     1500 '
      1510 IF FLAG2=0 AND FLAG3=0 AND FLAG4=0 AND FLAG5=0 AND FLAG6=0 AND FLAG7=0 ANI
      1520 PRINT #1, "SPEAKFILE=CALLHOS.MSG"
      1530 WHO$="+":NUMB=HOSP:GOSUB 2000
      1540 GOTO 1730 'OFFER TO MAKE ANOTHER CALL
      1550 LOOP=0
      1560 PRINT #1, "SPEAKFILE=TALK.MSG"
15     1570 FOR L=1 TO COUNT:TALK$=INKEY$:IF TALK$<>" " THEN 1580 ELSE NEXT L
      1580 IF TALK$="Y" THEN 1620 'PLACE PHONE CALL
      1590 IF TALK$="N" THEN 1800 'GO ON
      1600 IF LOOP>REPS THEN GOTO 1800 ELSE LOOP=LOOP+1
      1610 GOTO 1560
      1620 'SETUP PHONE CALL
      1630 LOOP=0:NUMB=0
      1640 PRINT #1, "SPEAKFILE=TALK2.MSG"
20     1650 FOR L=1 TO COUNT:WHO$=INKEY$:IF WHO$<>" " THEN 1660 ELSE NEXT L
      1660 IF WHO$="+" THEN NUMB=HOSP
      1670 IF WHO$="D" THEN NUMB=DOC 'DOCS PHONE NO.
      1680 IF WHO$="M" THEN NUMB=MARY 'MARYS PHONE NO.
      1690 IF NUMB>0 THEN GOTO 1720
      1700 IF LOOP>REPS THEN 1730 ELSE LOOP=LOOP+1
      1710 GOTO 1640
25     1720 GOSUB 2000
      1730 LOOP=0
      1740 PRINT #1, "SPEAKFILE=TALK3.MSG"
      1750 FOR L=1 TO COUNT:ANOTH$=INKEY$:IF ANOTH$<>" " THEN 1760 ELSE NEXT L
      1760 IF ANOTH$="Y" THEN GOTO 1620
      1770 IF ANOTH$="N" THEN GOTO 1800
      1780 IF LOOP>REPS THEN GOTO 1800 ELSE LOOP=LOOP+1
30     1790 GOTO 1740
      1800 PRINT #1, "SPEAKFILE=QUIET.MSG"
      1810 CLOSE #1:GOTO 560 ' LOOP AROUND AGAIN
      1820 'END
      1830 '
      1840 '
      1850 '
35     2000 'SUB TO PLACE PHONE CALL
      2005 '
      2010 GOTO 2900 'SKIP PHONE CALL
      2020 OPEN "COM2:1200,N,8,1" AS #2
      2030 PRINT #2, "ATDT";NUMB
      2040 LOOP=0:A$=""
      2050 B$=""
40     2060 B$=INPUT$(1,#2)
      2070 IF (ASC(B$)<48) OR (ASC(B$)>122) THEN 2050 ELSE LOOP=LOOP+1
      2080 IF LOOP<9 THEN 2050 ELSE A$=A$+B$
      2090 IF A$<>"CONNECT" THEN 2050
      2500 PRINT #2, CHR$(7), CHR$(7), CHR$(7)
      2510 'PRINT #2, "STEVE NEEDS ATTENTION"
      2520 PRINT #2, "H.A.N.C. NO. 33 LOCATION NO. 12"
      2530 PRINT #2, "PHONE 111-555-1212"
45     2540 PRINT #2, "BP : ";BPS;"/";BPD
      2550 PRINT #2, "PULSE : ";PULS
      2560 PRINT #2, "TEMPERATURE : ";TEMP

```

```

2800 CLOSE #2
2900 RETURN
3000 '
3010 'TEMP ROUTINE
3020 '
3030 'GOSUB 240          ' CALL ANALOG ASSEMB ROUTINE
3040 'TEMP=Y            'GET TEMP FROM REG. Y
3050 T=FIX(TEMP):DEC=CINT(10*(TEMP-FIX(TEMP)))/10 'TRUNC/ROUND TO TENTHS
3060 T=T+DEC
10 3070 PRINT #1, "SPEAKTEXT=YOUR TEMPERATURE IS";T;"DEGREES."
3080 IF TEMP>TLOW AND TEMP<THIGH THEN PRINT #1, "SPEAKFILE=TEMPOK.MSG":TLOOP=0:
3090 IF TLOOP=1 THEN 3130
3100 IF TEMP<TLOW THEN PRINT #1, "SPEAKFILE=TEMPLOW.MSG"
3110 IF TEMP>THIGH THEN PRINT #1, "SPEAKFILE=TEMPHI.MSG"
3120 TLOOP=1:RETURN 'REPEAT TEMP MEASURE
3130 'TEMP STILL OUT OF RANGE
15 : 10 TLOOP=0
3150 IF TEMP<TLOW THEN PRINT #1, "SPEAKFILE=TEMPLOW2.MSG":FLAG3=1:RETURN
3160 IF TEMP>THIGH THEN PRINT #1, "SPEAKFILE=TEMPHI2.MSG":FLAG4=1:RETURN
4000 '
4010 'BP/P ROUTINE
4020 '
4030 PLOOP=0
20 4040 'GOSUB 240          ' CALL ANALOG ASSEMB ROUTINE
4050 'PULS=X:BPS=V:BPD=W 'GET BLOOD PRESSURE AND PULSE FROM X,Y,W
4060 PRINT #1, "SPEAKTEXT=YOUR PULSE IS";PULS;" AND YOUR BLOOD PRESSURE IS";BPS
4070 IF PULS>PULSLO AND PULS<PULSHI THEN PRINT #1, "SPEAKFILE=PULSOK.MSG" ELSE
4080 FLAG7=0:FLAG8=0:GOTO 4140
4090 IF PLOOP<>0 THEN 4130
4100 IF PULS<PULSLO THEN PRINT #1, "SPEAKFILE=PULSLO.MSG":FLAG7=1
4110 IF PULS>PULSHI THEN PRINT #1, "SPEAKFILE=PULSHI.MSG":FLAG8=1
25 4120 PLOOP=PLOOP+1:GOTO 4050 'REPEAT PULSE/BP
4130 'STILL OUT OF RANGE GO ON TO BP
4140 'GO ON TO BP
4150 IF (BPS>SYSLO AND BPS<SYSHI) AND (BPD>DILO AND BPD<DIHI) THEN PRINT #1, "S
4160 IF BPS>SYSLO OR BPD<DILO THEN PRINT #1, "SPEAKFILE=BPLO.MSG" ELSE 4180
4170 FLAG5=1:RETURN
4180 'BP SHOULD BE HIGH
30 4190 PRINT #1, "SPEAKFILE=BPHI.MSG"
4200 FLAG6=1:RETURN

```

35 Claims

1. An interactive assistance providing apparatus comprising:
 - a housing;
 - control means carried by said housing;
 - means, carried by said housing and coupled to said control means, for synthesizing audible sounds in response to commands from said control means;
 - means, carried by said housing and coupled to said control means, for dispensing a deliverable product in response to commands from said control means;
 - means actuated by said control means for delivery of said dispensed product;
 - means, carried by said housing and coupled to said control means for initiating selected diagnostic tests in accordance with a predetermined, prestored schedule; and
 - means, coupled to said control means for receiving results of said selected tests with said control means including means for generating a reminder sequence of commands to said synthesizing means for producing an audible reminder message in response to a prestored schedule and for providing dispensing commands to said dispensing means.
2. An apparatus as in claim 1 including:
 - means for generating a reminder sequence of commands to said synthesizing means for producing an audible diagnostic test initiation reminder message in response to said prestored schedule and for providing selected test initiation commands to said test initiation means.
3. An apparatus as in claim 1 including means, carried by said housing and coupled to said control means, for moving said housing in a selected direction.
4. An apparatus as in claim 3 including obstacle detecting means carried by said housing.

5. An apparatus as in claim 1 including means, coupled to said control means and carried by said housing, for recognizing at least selected audible words.

6. An apparatus as in claim 5 wherein said recognizing means includes means for recognizing selected audible words spoken by at least two different individuals.

7. An apparatus as in claim 5 including means for attempting to complete an audio telecommunications link with a remote location in response to selected recognized words.

8. An apparatus as in claim 5 with said diagnostic tests selected from a group including at least blood pressure measurement; pulse rate measurement; and corporal body temperature measurement.

9. An apparatus as in claim 1 further including means for displaying selected information.

10. An apparatus as in claim 1 including means, actuated by said control means for delivery of said selected diagnostic test implement for use.

11. An apparatus as in claim 1 including means, carried by said housing and coupled to said control means, for detecting and recognizing at least a predetermined plurality of audible sounds.

12. An apparatus as in claim 10 with said delivery means including electrically actuated release means for effecting delivery of said selected diagnostic test implement for use.

13. An apparatus as in claim 10 including a moveable test implement supporting member.

14. An apparatus as in claim 13 with said supporting member moveable from a first, closed, to a second, delivery position.

15. An apparatus as in claim 14 including biasing means for urging said supporting member from said first to said second position.

16. An apparatus as in claim 1 with said dispensing means including a housing defining a deliverable product containing volume.

17. An apparatus as in claim 16 with said delivery means supported, at least in part, adjacent said housing and including means for movement of a selected quantity of the deliverable product from a position adjacent said housing to a delivery position.

18. An apparatus as in claim 1 with said control means including means for altering said predetermined, prestored schedule.

19. An apparatus as in claim 1 including a plurality of moveable containers moveable from a first, closed, position to a second, open, position in response to electrical signals generated by said control means.

20. An interactive system comprising:
a housing;

control means carried by said housing;

means, carried by said housing and coupled to said control means, for detecting and recognizing at least a predetermined plurality of audible sounds;

means, carried by said housing and coupled to said control means, for synthesizing audible sounds in response to commands from said control means;

means, carried by said housing and coupled to said control means for dispensing selected products in response to commands from said control means;

means, carried by said housing and coupled to said control means for initiating selected diagnostic tests in accordance with a predetermined, prestored schedule;

means, actuatable by said control means, for delivery of selected diagnostic test apparatus from a stored condition to a use condition;

means, coupled to said control means for receiving results of said selected tests with said control means including means for generating a reminder sequence of commands to said synthesizing means for producing an audible reminder message in response to a prestored schedule and for then providing dispensing commands to said dispensing means;

means for moving said housing in response to commands from said control means; and

obstacle detecting means, carried by said housing and coupled to said control means for providing information as to the presence of obstacles to said moving housing.

21. A system as in claim 20 including means for establishing a telecommunications path between the system and a remote location.

22. A system as in claim 21 including means for providing a sequence of prestored diagnostically related information for transmission to the remote location.

23. A system as in claim 21 including means for conducting a verbal conversation with the remote location using said telecommunications path.

24. A system as in claim 20 including timing means, coupled to said control means, for proving an alarm indicium in response to a prestored schedule.

25. A system as in claim 20 with said initiating means including:
means for determining temperature of a selected corporal body.

26. A system as in claim 20 with said initiating means including:
means for determining selected fluid pressures of a corporal body.

5 27. A system as in claim 20 with said control means including a programmed computer.

28. A system as in claim 10 including means actuatable by said control means for delivery of said
dispensed product.

29. A system as in claim 28 including releasable and moveable means for supporting said dispensed
product.

10 30. An interactive assistance providing apparatus comprising:

a housing;

control means carried by said housing;

means, carried by said housing and coupled to said control means, for synthesizing audible sounds in
response to commands from said control means;

15 means, carried by said housing and coupled to said control means, for dispensing medication in response
to commands from said control means;

means actuated by said control means for delivery of said dispensed medication;

means, carried by said housing and coupled to said control means for initiating selected diagnostic tests in
accordance with a predetermined, prestored schedule; and

20 means, coupled to said control means for receiving results of said selected tests with said control means
including means for generating a reminder sequence of commands to said synthesizing means for
producing an audible medication taking reminder message in response to a prestored schedule and for
providing dispensing commands to said dispensing means.

25 31. An apparatus as in claim 30 including means for detecting and recognizing at least a plurality of
audible sounds.

30

35

40

45

50

55

7.03.89

Nouveau dispositif de mesure
Nouvellement d'usage





Fig. 1

Fig. 2






Fig. 3




Fig. 4

Neu eingereicht!
Nein!

17-10-99




Fig. 5




Fig. 6








Fig. 8



12 00 00




Fig. 11a

Neu eingeleitet
Neuvellement




Fig. 11b

17 00 00




Fig. 11c

17 08 89




Fig. 11d






Fig. 11e








Fig. 14a

THIS PAGE BLANK (USPTO)

7-09-89

1989-09-01
1989-09-01
1989-09-01




Fig. 1




Fig. 2




Fig. 3

17 00 00




Fig. 4

17-03-89

New design right /
Not in use




Fig. 5









Fig. 6

7.08.89





1700 21




Fig. 11a

Non classifié
Nouvellement




Fig. 11b

1708 00




Fig. 11c

1708 88




Fig. 11d

7-08-89




Fig. 11e




Fig. 12





Fig. 13



(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:

0 342 859 A3

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 89304779.5

(51) Int. Cl.⁵: G06F 15/42

(22) Date of filing: 11.05.89

(30) Priority: 12.05.88 US 194018
02.06.88 US 201779

(43) Date of publication of application:
23.11.89 Bulletin 89/47

(84) Designated Contracting States:
AT CH DE ES FR GB GR IT LI NL SE

(68) Date of deferred publication of the search report:
11.03.92 Bulletin 92/11

(71) Applicant: **HEALTH TECH SERVICES CORPORATION**
255 Revere Drive Suite 120
Northbrook Illinois(US)

(72) Inventor: **Kaufman, Stephen B.**
1939 Lewis Avenue
Highland Park Illinois 60035(US)
Inventor: **Hyland, Shelly**
4619 Daisy
Crystal Lake Illinois 60012(US)
Inventor: **Lesczynski, Michael A.**
17 Stonefield Place
Honeoye Falls, New York 14472(US)
Inventor: **Bryant, Cal L.**
718 Morning Glory Lane
Bartlett Illinois 60103(US)

(74) Representative: **MacGregor, Gordon et al**
ERIC POTTER & CLARKSON St. Mary's Court
St. Mary's Gate
Nottingham, NG1 1LE(GB)

(54) Interactive patient assistance system.

(57) A system is provided for interactively assisting a patient. The system includes a speech synthesizer and recognition unit coupled to a programmed computer. The computer can keep track of a medication and diagnostic testing schedule. The system also includes diagnostic testing equipment coupled to the computer along with medication dispensing equipment. In accordance with a predetermined schedule, the system verbally communicates with the patient,

prompts the patient through the various steps necessary to carry out the diagnostic testing and further prompts patient at appropriate times for taking medication. The medication is also provided in combination with the verbal prompts. The system also provides access to a telecommunications link in response to verbal requests of the patient and in one embodiment can move in a limited area adjacent the patient.




Fig. 3

EP 0 342 859 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 89 30 4779

Page 1

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.4)
Y	PROCEEDINGS OF THE 8TH ANNUAL SYMPOSIUM ON COMPUTER APPLICATION IN MEDICAL CARE; IEEE COMPUTER SOCIETY PRESS, WASHINGTON DC, US; 4 November 1984, WASHINGTON DC, US; pages 886 - 891; SANDERS, S.J.; SHEPPARD, A.P.; SPURLOCK, J.M.: 'MICROCOMPUTER CONTROLLED CARE SYSTEM FOR THE SEVERELY PHYSICALLY IMPAIRED' * page 886, left column, line 4 - line 13 * * page 886, left column, line 37 - line 45 * * page 886, right column, line 1 - line 10 * * page 886, right column, line 22 - line 35 * * page 887, left column, line 8 - line 21 * * page 887, left column, line 35 - line 40 * * page 887, left column, line 60 - right column, line 5 * * page 887, right column, line 52 - page 888, left column, line 14 * * page 888, left column, line 42 - right column, line 10 * * page 888, right column, line 36 - line 45 * ---	1-31	G06F15/42
Y	PROCEEDINGS OF THE 10TH ANNUAL CONFERENCE ON REHABILITATION TECHNOLOGY; RESNA ASS. ADV. REHABILITATION TECHN, 1987; 19 June 1987, SAN DIEGO, CA, US; pages 796 - 798; LEES, D.; CRIGLER, B.; VANDERLOOS, M.; LEIFER, L.J.: 'DESIGN OF THE SECOND GENERATION DESK-TOP ROBOTIC AID' * page 796, left column, line 1 - line 24 * * page 796, right column, line 22 - line 26 * * page 797, left column, line 19 - line 22 * * page 797, right column, line 17 - line 21 * --- -/--	1-31	TECHNICAL FIELDS SEARCHED (Int. Cl.4) G06F
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 14 JANUARY 1992	Examiner BARBA M.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document			

EPO FORM 1503 03.92 (P0401)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 89 30 4779
Page 2

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.4)
A	EP-A-0 251 520 (BUDDY SYSTEMS, INC., ILLINOIS, US) 7 January 1988 * page 2, line 29 - line 50 * * page 3, line 18 - line 46 * * page 4, line 35 - line 43 * * page 4, line 53 - line 55 * * page 5, line 3 - line 5 * * page 5, line 25 - line 26 * * page 11, line 43 - line 47 * ---	1,2, 7-10,12, 18, 20-27,30	
A	US-A-4 695 954 (R.J. ROSE; R.L. TRIMBLE) 22 September 1987 * column 3, line 1 - line 35 * * figure 1 * ---	7,16,17, 19,21, 27-30	
A	ELECTRONICS TIMES no. 284, 27 September 1984, pages 24 - 25; PETROSKY, M.: 'ROBOTS LEND AN HELPING HAND TO DISABLED' * page 24, column 1, line 5 - line 8 * * page 24, column 3, line 15 - line 35 * * page 24, column 3, line 50 - line 64 * * page 24, column 4, line 31 - line 67 * * page 25, column 1, line 17 - line 35 * * page 25, column 2, line 2 - line 5 * * page 25, column 2, line 36 - line 51 * * page 24; figure 1 * ---	1,3-6, 11,13, 19,20, 29,31	TECHNICAL FIELDS SEARCHED (Int. Cl.4)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 14 JANUARY 1992	Examiner BARBA M.
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document	

EPO FORM 1503 (01.82) (P.0401)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 89 30 4779

Page 3

DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.4)
A	PROCEEDINGS OF THE 1978 IEEE CONFERENCE ON DECISION AND CONTROL; IEEE COMPUTER SOCIETY PRESS; 10 January 1979, SAN DIEGO, CA, US; pages 1423 - 1428; LEE, C.S.G.; CAMPBELL, J.; SARIOIS, G.: 'VOICE CONTROLLED TRAINABLE MANIPULATORS WITH VISUAL FEEDBACK' * page 1423, left column, line 11 - line 15 * * page 1423, left column, line 29 - line 33 * * page 1424, left column, line 5 - line 18 * * page 1424, left column, line 45 - line 67 * -----	1, 4-6, 11, 20, 30-31	
			TECHNICAL FIELDS SEARCHED (Int. Cl.4)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 14 JANUARY 1992	Examiner BARBA M.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 150 01.82 (P0401)